

Wood filler gel



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare
Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be

PRODUCT DESCRIPTION

To join gaps in wooden floors. Mix the gel with sanding dust coming from the to be treated wood.

TECHNICAL DATA

APPEARANCE	thick uncoloured liquid
VISCOSITY	180 sec/DIN 4 mm with 20°C
DENSITY	0,9

USE

To fill nail-holes. To close up wooden floors. To repair old brays of oak. For all sorts of wooden repairs.

PREPARATION

Make a mixture with the Woodfiller Gel and the sanding-dust (P 100-120)of the wood that has to be treated. Notice that you use less Woodfiller Gel than sanding-dust, the woodfiller gel is only a binder.

USER TIPS

Apply the paste with putty-knife. Conserve always in a sealed tin.



DRYING TIMES

Sandable after +/- 30 minutes.

AFTER TREATMENT

When the Wood filler is dry, sand with grid P100.

PRODUCT INFORMATION

Storage: 2 years in closed packing.

SPECIAL QUALITIES

Wood filler gel contains products that restrain shrinkage.